

Specifications

General

Frequency Bands	VHF:136-174MHz UHF1:400-470MHz UHF3:350-400MHz
Channel Capacity	1024
Channel Space	12.5/20/25KHz
Dimensions(H*W*D)	125*54*35mm
Weight	320g (With standard battery and antenna)
Operating Voltage	DC 7.4V
Battery	2400mAh(Li-ion)
Battery Life (5-5-90 Duty Cycle, High TX Power)	Analog: 13H(No GPS) 11.5H(With GPS) Digital: 15H(No GPS) 13H(With GPS)

Transmitter

Frequency Stability	0.5ppm
RF Power Output	VHF:High 5W Low:1W UHF:High 4.2W Low:1.2W
Digital Modulation	7K60FXD (Data Only) 7K60FXW (Data and Voice)
Analog Modulation	16K ∅F3E @ 25KHz /14K ∅F3E @ 20KHz /11K ∅F3E @ 12.5KHz
4FSK Modulation Accuracy	5%
4FSK TX BER	0%
4FSK and Magnitude Error	5% / 1%
Adjacent Channel Power	70dB @ 25/20 KHz / 60dB @ 12.5 KHz
Conducted and Radiated Emission	-36dBm <1GHz / -30dBm >1GHz
Transmission Deviation limits	5KHz@25KHz / 4KHz@20KHz /2.5KHz@12.5KHz
Audio Distortion	3%
Hum and Noise	48dB @ 25KHz / 46dB@20KHz / 43dB @ 12.5KHz
Audio Response	+1 ~ -3dB

Receiver

Digital Sensitivity	-120dBm / BER 5% -116dBm / BER 1%
Digital Dynamic Faded Sensitivity (100KM/H& 8KM/H Rayleigh Fading)	-104dBm
Analog Sensitivity	-120dBm / 12dB SINAD
Intermodulation	70dB (TIA603) 65dB (ETSI)
Blocking	90dB (TIA603 & ETSI)
Spurious Response Rejection	75dB (TIA603 & ETSI)
Adjacent Channel Selectivity	75dB@25 KHz (TIA603) 70dB@25 KHz (ETSI) 70dB@20KHz (TIA603 & ETSI) 65dB@12.5KHz (TIA603) 60dB@12.5 KHz (ETSI)
Conducted Spurious Emission	-57dBm
Rated Audio Power Output	1W
Rated Audio Distortion	3%
Hum and Noise	48dB @25KHz / 46dB@20KHz / 43dB@12.5KHz
Audio Response	+1 ~ -3dB
Digital Vocoder Type	AMBE++
Digital Protocol	ETSI-TS102 361 -1, -2,-3,-4

Reliability

Operating Temperature	-30 ~ +60 °C
Storage Temperature	-40 ~ +85 °C
Dust & Water Intrusion	IP67 (IEC60529)
Humidity	MIL-STD-810 C/D/E/F/G Standard
Shock&Vibration	MIL-STD-810 C/D/E/F/G Standard
ESD	IEC 61000-4-2(level 4) ±8KV(Contact) , ±15KV(Air)

GPS&GLONASS

TIFF Cold Start	60s
TIFF Hot Start	10s
Horizontal Positioning Accuracy	10m

Standard Accessories :



Pictures above are for reference only and may vary from actual products.



SHENZHEN EXCERA TECHNOLOGY CO.,LTD.

www.excera.com.cn



EXCERA

Innovate to Succeed

DMR Portable Radio EP8000

- ◆ Full Duplex Communications
- ◆ Superior Digital Voice with High-Power Loudspeaker
- ◆ IP67 and MIL-STD-810 Standard Compliance
- ◆ DMR Tier II Conventional and DMR Tier III Trunking



Advantage Features

Superior Digital Voice

Built in 2W high-power loudspeaker, ensuring the clear and crisp voice communications. With the adoption of narrowband codec and digital error-correction technologies, EP8000 is capable of ensuring your superior voice in the noise environment or at the edge of the coverage area.




High Capacity Battery Design

Equipped with 2400mAh or 3400mAh high capacity Panasonic Li-ion battery to make sure the radio's usage life.




Built-in Bluetooth(Optional)

Equipped Bluetooth inside radio ,ensuring the expanding applications such as BT accessories, BT wirelss programming and other applications.




Built-in Noise Reduction Function (Optional)

Featured with advanced noise reduction which makes the noise suppression be up to 25dB.



Full- duplex calling (Optional)

Full duplex calling allows for natural and intuitive communications without push-to-talk(only in trunking mode).



Built –in GPS (Optional)



DMR Tier III Support

Supports DMR Tier III just by software upgrade and makes the radio applications more rich and more advanced.



Rich API Support


Rich API supports the user or third party to develop supplemental applications.



Advantage Features

IP67 and MIL-STD-810 Standards Compliance

EP8000 is compliant with the MIL- STD -810- G and IP67 (IEC60529) standard, ensuring outstanding performance even in harsh environment.



Main Functions

DMR Conventional

- | | | | | |
|---|--|---|---|--|
| Radio Function
› Direct/Repeat Mode
› SCAN
› Bluetooth 4.0
› Audio Feedback Suppression
› TDMA Direct Mode
› Multi-site Roaming
› Excera Capacity Added | Voice Service
› Group Call
› Private Call
› All Call
› Emergency Call
› Broadcast Call
› Phone call | Data Service
› Text Messaging
› Status Messaging | Supplementary Service
› Call Alert
› Radio Check
› Remote Monitor
› Radio Enable/Disable /Kill

Safety Function
› DMRA Encryption
› Transmit Interrupt
› Lone Worker
› Man Down | Location Service (optional)
› GPS
› Beidou
› GLONASS |
|---|--|---|---|--|

Analog Conventional Signaling

- › CTCSS&CDCSS
- › 5-tone
- › MDC1200

DMR Tier III and MPT Trunking (Software Licensed)

Optional Accessories

Remote Speaker Microphone EMRN011	Wireless Remote Speaker Microphone EMRW011	C Style Earpiece EEHN011	1-Wire Earpiece with Transparent Acoustic Tube EEAN011	2-Wire Earpiece with Transparent Acoustic Tube EEAN021	Police Full Bone Conduction Headset EEBN011	Fireman Full Bone Conduction Headset EEBN021
Bluetooth Headset EEWB03E	Wireless PTT EPTTB01	3400 mAh Battery EB342L	Multi-unit Charger EMC702L	Programming Cable EPC01	Leather Case ELBY01	

Excera retains right to change the products design and specification without prior notice. Parts supply for the market is different, please contact the local dealer. Promotional photos are for reference only. All products as per the material subjects.